

# Autonics



Фотоелектричні датчики  
Каталог 2023

# A1. Photoelectric Sensors

Photoelectric sensors are used to detect distance, absence or presence of objects using a light transmitter and receiver.

A1-1	Rectangular	BTS Series	W 7.2 mm Photoelectric Sensors
		BJ Series	Rectangular Photoelectric Sensors (Cable Type)
			Rectangular Photoelectric Sensors (Connector Type)
		BJX Series	Rectangular Photoelectric Sensors
		BM Series	General Photoelectric Sensors
		BMS Series	Side Sensing Photoelectric Sensors
		BY Series	Photoelectric Sensors with Synchronous Detection
		BYD Series	Photoelectric Sensors with Built-In Timer
		BH Series	Front / Side Mount Photoelectric Sensors
A1-2	Compact	BA Series	Diffuse Reflective Long-Distance Photoelectric Sensors
		BTF Series	L 3.7 mm Flat Photoelectric Sensors
		BPS Series	L 7.5 mm Flat Photoelectric Sensors
A1-3	Cylindrical	BRQ Series	Cylindrical Photoelectric Sensors (Front Sensing Type)
			Cylindrical Photoelectric Sensors (Side Sensing Type)
		BR Series	Cylindrical Photoelectric Sensors
A1-4	U-Shaped	BUM Series	4-Channel U-Shaped Photoelectric Sensors
		BUP Series	1-Channel U-Shaped Photoelectric Sensors
A1-5	AC / DC	BEN Series	Universal AC / DC Photoelectric Sensors
		BX Series	Universal AC / DC Photoelectric Sensors
A1-6	PCB Detection	BJP Series	Photoelectric Sensors for PCB Detection
A1-7	Oil-Resistant / Oil-Proof	BJR Series	Oil-Resistant Photoelectric Sensors
		BJR-F Series	Oil-Proof Photoelectric Sensors
A1-8	Color Mark	BC Series	Color Mark Photoelectric Sensors
A1-9	Liquid Level	BL Series	Liquid Level Photoelectric Sensors

# W 7.2 mm

## Photoelectric Sensors

### BTS Series



#### Features

- W 7.2 mm Photoelectric Sensors
  - W 7.2 × H 18.6 × L 9.5 mm (Through-beam type)
  - W 7.2 × H 24.6 × L 10.8 mm (Retroreflective, convergent reflective type)
- Detection methods and minimum target size
  - Through-beam type (BTS1M): Ø 2 mm
  - Retroreflective type (BTS200): Ø 2 mm (sensing distance: 100 mm)
  - Convergent reflective type (BTS15/BTS30): Ø 0.15 mm (sensing distance: 10 mm)
- Maximum sensing distance:  
1 m (Through-beam type)
- Operation indicator (red) and stability indicator (green) show operation status
- Stainless steel (SUS304) mounting brackets
- IP67 protection rating (IEC standard)

#### Specifications

Model	BTS1M-TDT□-□	BTS200-MDT□-□	BTS□-LDT□-□
Sensing type	Through-beam	Retroreflective	Convergent reflective
Sensing distance	1 m	10 to 200 mm <sup>01)</sup>	5 to 15 mm <sup>02)</sup> 5 to 30 mm <sup>02)</sup>
Sensing target	Opaque materials	≥ Ø 27 mm Opaque materials	Opaque materials, translucent materials
Min. sensing target	≥ Ø 2 mm	≥ Ø 2 mm <sup>03)</sup>	≥ Ø 0.15 mm <sup>04)</sup>
Hysteresis	-	-	≤ 15 % of sensing distance
Response time	≤ 1 ms		
Light source	Red LED		
Peak emission wavelength	650 nm		
Operation mode	Light ON mode / Dark ON mode model		
Indicator	Operation indicator (red), stability indicator (green)		
Approval	CE ENEC	CE ENEC	CE ENEC
Unit weight (packaged)	≈ 40 g (≈ 65 g)	≈ 25 g (≈ 45 g)	≈ 25 g (≈ 45 g)

01) Reflector (MS-6)

02) Non-glossy white paper 50 × 50 mm

03) Sensing distance 100 mm

04) Sensing distance 10 mm

Power supply	12-24 VDC≡ ±10 % (ripple P-P: ≤ 10%)
Current consumption	It depends on the sensing type
Through-beam	Emitter: ≤ 20 mA, receiver: ≤ 20 mA
Reflective	≤ 20 mA
Control output	NPN open collector output / PNP open collector output model
Load voltage	≤ 26.4 VDC≡
Load current	≤ 50 mA
Residual voltage	NPN : ≤ 1 VDC≡, PNP : ≤ 2 VDC≡
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC≡ megger)
Noise immunity	±240 VDC≡ the square wave noise (pulse width: 1 μs) by the noise simulator
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times
Ambient illuminance (receiver)	Sunlight: ≤ 10,000 lx, incandescent lamp: ≤ 3,000 lx
Ambient temperature	-20 to 55 °C, storage: -30 to 70 °C (no freezing or condensation)
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)
Protection rating	IP67 (IEC standard)
Connection	Cable type
Cable spec.	Ø 2.5 mm, 3-wire (emitter: 2-wire), 2 m
Wire spec.	AWG 28 (0.08 mm, 19-core), insulator outer diameter: Ø 0.9 mm
Material	Case: PBT, sensing part: PMMA, bracket: SUS304, bolt: SWCH10A



View product detail

# Rectangular Photoelectric Sensors (Cable Type)

## BJ Series



### Features

- Compact size: W 10.6 × H 32 × L 20 mm
- IP65 protection rating (IEC standard)
- Adjuster for selecting Light ON / Dark ON mode
- Built-in sensitivity adjustment adjuster (except BJG30-DDT)
- Reverse power protection circuit, output short overcurrent protection circuit
- Mutual interference prevention function (except through-beam and BGS reflective type)
- Excellent noise immunity and minimal influence from ambient light

### Specifications

Model	BJ□-TDT-□			BJ3M-PDT-□	BJ□-BDT-□		BJN□-NDT-□	
Sensing type	Through-beam			Polarized retroreflective	BGS reflective		Narrow beam reflective	
Sensing distance	7 m	10 m	15 m	3 m <sup>01)</sup>	10 to 30 mm <sup>02)</sup>	10 to 50 mm <sup>02)</sup>	30 to 70 mm <sup>03)</sup>	70 to 130 mm <sup>03)</sup>
Sensing target	Opaque materials			Opaque materials	Opaque materials, translucent materials		Opaque materials, translucent materials	
Min. sensing target	≥ Ø 8 mm	≥ Ø 12 mm		≥ Ø 75 mm	-		≥ Ø 0.2 mm (copper wire)	
Hysteresis	-			-	≤ 10% of sensing distance		≤ 25% of sensing distance	≤ 20% of sensing distance
Black/white difference	-			-	≤ 10% of sensing distance		-	
Response time	≤ 1 ms			≤ 1 ms	≤ 1.5 ms		≤ 1 ms	
Light source	Red	Red	Infrared	Red	Red		Red	
Peak emission wavelength	650 nm	660 nm	850 nm	660 nm	660 nm		650 nm	
Min. spot size	-			-	≈ Ø 5.0 mm	≈ Ø 4.5 mm	≈ Ø 2.0 mm	≈ Ø 2.5 mm
Sensitivity adjustment	YES (Adjuster)			YES (Adjuster)	YES (Adjuster) <sup>04)</sup>		YES (Adjuster)	
Mutual interference prevention	-			YES	-		YES	
Operation mode	Light ON mode - Dark ON mode selectable (Adjuster)							
Indicator	Operation indicator (red), stability indicator (green), power indicator (green) <sup>05)</sup>							
Approval	CE ENEC			CE ENEC	CE ENEC		CE ENEC	
Unit weight (packaged)	≈ 90 g (≈ 115 g)			≈ 60 g (≈ 85 g)	≈ 50 g		≈ 45 g	

01) Reflector (MS-2A)

02) Non-glossy white paper 50 × 50 mm

03) Non-glossy white paper 100 × 100 mm

04) -10% of max. sensing distance, Non-glossy white paper

05) Only for the emitter



View product detail

Next Page ►

Model	BJ□-DDT-□			BJG30 -DDT
Sensing type	Diffuse reflective			Diffuse reflective
Sensing distance	100 mm <sup>01)</sup>	300 mm <sup>01)</sup>	1 m <sup>02)</sup>	15 mm <sup>03)</sup> or 30 mm <sup>01)</sup>
Sensing target	Opaque materials, translucent materials			Transparent glass or opaque materials, translucent materials
Hysteresis	≤ 20% of sensing distance			≤ 20% of sensing distance
Response time	≤ 1 ms			≤ 1 ms
Light source	Infrared	Red	Infrared	Infrared
Peak emission wavelength	850 nm	660 nm	850 nm	850 nm
Sensitivity adjustment	YES (Adjuster)			-
Mutual interference prevention	YES			YES
Operation mode	Light ON mode - Dark ON mode selectable (Adjuster)			Light ON
Indicator	Operation indicator (red), stability indicator (green)			Operation indicator (red), stability indicator (green)
Approval	CE EAC			CE EAC
Unit weight (packaged)	≈ 45 g (≈ 70 g)			≈ 45 g

01) Non-glossy white paper 100 × 100 mm

02) Non-glossy white paper 300 × 300 mm

03) Transparent Glass 50 × 50 mm, t = 3.0 mm

Power supply	12-24 VDC≡ ±10 % (ripple P-P: ≤ 10%)
Current consumption	It depends on the sensing type
Through-beam	Emitter: ≤ 20 mA, receiver: ≤ 20 mA
Reflective	≤ 30 mA
Control output	NPN open collector output / PNP open collector output model
Load voltage	≤ 26.4 VDC≡
Load current	≤ 100 mA
Residual voltage	NPN : ≤ 1 VDC≡, PNP : ≤ 2.5 VDC≡ (BGS reflective type : ≤ 2 VDC≡)
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC≡ megger)
Noise immunity	±240 VDC≡ the square wave noise (pulse width: 1 μs) by the noise simulator
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx
Ambient temperature	-25 to 55 °C, storage: -40 to 70 °C (no freezing or condensation)
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)
Protection rating	IP65 (IEC standard)
Connection	Cable type
Cable spec.	Ø 3.5 mm, 3-wire (emitter: 2-wire), 2 m
Wire spec.	AWG24 (0.08 mm, 40-core), insulator outer diameter: Ø 1 mm
Material	Case: PC+ABS, CAP: PC, sensing part: PMMA, bracket: SUS304, bolt: SCM, nut: SCM, sleeve: Brass, Ni-plate

# Rectangular Photoelectric Sensors (Connector Type)

## BJ Series



### Features

- Compact size: W 10.6 × H 32 × L 20 mm
- IP67 protection rating (IEC standard)
- Adjuster for selecting Light ON / Dark ON mode
- Built-in sensitivity adjustment adjuster
- Reverse power protection circuit, output short overcurrent protection circuit
- Mutual interference prevention function
- Excellent noise immunity and minimal influence from ambient light
- High performance lens with long sensing distance
- Long sensing distance :  
Through-beam type 15 m,  
diffuse reflective type 1 m,  
polarized retroreflective type 3 m (MS-2A)
- M.S.R. (Mirror Surface Rejection) function (Polarized retroreflective type)



View product detail

### Specifications

Model	BJ□-TDT-C-□		BJ3M-PDT-C-□	BJ□-DDT-C-□		
Sensing type	Through-beam		Polarized retroreflective	Diffuse reflective		
Sensing distance	10 m	15 m	3 m <sup>01)</sup>	100 mm <sup>02)</sup>	300 mm <sup>03)</sup>	1 m <sup>03)</sup>
Sensing target	Opaque materials		Opaque materials	Opaque materials, translucent materials		
Min. sensing target	≥ Ø 12 mm		≥ Ø 75 mm	-		
Hysteresis	-		-	≤ 20% of sensing distance		
Response time	≤ 1 ms		≤ 1 ms	≤ 1 ms		
Light source	Red	Infrared	Red	Infrared	Red	Infrared
Peak emission wavelength	660 nm	850 nm	660 nm	850 nm	660 nm	850 nm
Sensitivity adjustment	YES (Adjuster)		YES (Adjuster)	YES (Adjuster)		
Mutual interference prevention	-		YES	YES		
Operation mode	Light ON mode - Dark ON mode selectable (Adjuster)					
Indicator	Operation indicator (red), stability indicator (green), power indicator (green) <sup>04)</sup>					
Approval	CE ENEC		CE ENEC	CE ENEC		
Unit weight (packaged)	≈ 20 g (= 45 g)		≈ 30 g (= 55 g)	≈ 10 g (= 35 g)		

01) Reflector (MS-2A)

02) Non-glossy white paper 100 × 100 mm

03) Non-glossy white paper 300 × 300 mm

04) Only for the emitter

Power supply	12-24 VDC≡ ±10 % (ripple P-P: ≤ 10%)
Current consumption	It depends on the sensing type
Through-beam	Emitter: ≤ 20 mA, receiver: ≤ 20 mA
Reflective	≤ 30 mA
Control output	NPN open collector output / PNP open collector output Model
Load voltage	≤ 26.4 VDC≡
Load current	≤ 100 mA
Residual voltage	NPN: ≤ 1 VDC≡, PNP: ≤ 2.5 VDC≡
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC≡ megger)
Noise immunity	±240 VDC≡ the square wave noise (pulse width: 1 μs) by the noise simulator
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx
Ambient temperature	-25 to 55 °C, storage: -40 to 70 °C (no freezing or condensation)
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)
Protection rating	IP67 (IEC standard)
Connection	Connector type
Connector	M8 4-pin plug type
Material	Case: PC+ABS, CAP: PC, sensing part: PMMA, bracket: SUS304, bolt: SCM, nut: SCM, sleeve: Brass, Ni -plate

# Rectangular Photoelectric Sensors

## BJX Series



### Features

- Long sensing distance with high quality lens:  
Through-beam type 30 m,  
diffuse reflective type 1 m,  
polarized retroreflective type 3 m (MS-2A)
- M.S.R. (Mirror Surface Rejection) function  
(Polarized retroreflective type)
- Compact size : W 11 × H 32 × L 20 mm
- Switch for selecting Light ON/Dark ON mode
- Built-in sensitivity adjustment adjuster
- Reverse power protection circuit,  
output short overcurrent protection circuit
- Mutual interference prevention function  
(except through-beam type)
- Excellent noise immunity and  
minimal influence from ambient light
- IP65 protection rating (IEC standard)

### Specifications

Model	BJX□-TDT-□-□			BJX3M-PDT-□-□	BJX□-DDT-□-□		
Sensing type	Through-beam			Polarized retroreflective	Diffuse reflective		
Sensing distance	10 m	15 m	30 m	3 m <sup>01)</sup>	100 mm <sup>02)</sup>	300 mm <sup>02)</sup>	1 m <sup>03)</sup>
Sensing target	Opaque materials			Opaque materials	Opaque materials, translucent materials		
Min. sensing target	≥ Ø 15 mm			≥ Ø 75 mm	-		
Hysteresis	-			-	≤ 20 % of sensing distance		
Response time	≤ 1 ms						
Light source	Red	Infrared	Red	Red	Infrared	Red	Red
Peak emission wavelength	660 nm	850 nm	660 nm	660 nm	850 nm	660 nm	660 nm
Sensitivity adjustment	YES (Adjuster)			YES (Adjuster)	YES (Adjuster)		
Mutual interference prevention	-			YES	YES		
Operation mode	Light ON mode - Dark ON mode selectable (Adjuster)						
Indicator	Operation indicator (yellow), stability indicator (green), power indicator (red) <sup>04)</sup>						
Approval	CE  EAC			CE  EAC	CE  EAC		

01) Reflector (MS-2A)

02) Non-glossy white paper 100 × 100 mm

03) Non-glossy white paper 300 × 300 mm

04) Only for the emitter

Unit weight (packaged)	Through-beam	Polarized retroreflective	Diffuse reflective
Cable type	≈ 95 g (≈ 145 g)	≈ 50 g (≈ 115 g)	≈ 50 g (≈ 100 g)
Connector type	≈ 12 g (≈ 65 g)	≈ 6 g (≈ 75 g)	≈ 6 g (≈ 60 g)
Power supply	10-30 VDC≒ ±10 % (ripple P-P: ≤ 10 %)		
Current consumption	It depends on the sensing type		
Through-beam	Emitter: ≤ 20 mA, receiver: ≤ 20 mA		
Reflective	≤ 30 mA		
Control output	NPN open collector output / PNP open collector output model		
Load voltage	≤ 30 VDC≒		
Load current	≤ 100 mA		
Residual voltage	NPN: ≤ 1 VDC≒, PNP: ≤ 2 VDC≒		
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit		
Insulation resistance	≥ 20 MΩ (500 VDC≒ megger)		
Noise immunity	±240 VDC≒ the square wave noise (pulse width: 1 μs) by the noise simulator		
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min		
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours		
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times		
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx		
Ambient temperature	-25 to 60 °C, storage: -40 to 70 °C (no freezing or condensation) <sup>01)</sup>		
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)		
Protection rating	IP65 (IEC standard)		
Connection	Cable type / Connector type model		
Cable spec.	Ø 4 mm, 3-wire (Emitter: 2-wire), 2 m		
Wire spec.	AWG26 (0.52 mm, 20-core), insulator outer diameter: Ø 1 mm		
Connector	M8 4-pin plug type		
Material	Case: PC, CAP: PC, sensing part: PMMA		

01) UL approved ambient temperature: 40 °C



View product detail

# General

## Photoelectric

## Sensors

### BM Series



#### Features

- Easy to mount at a narrow space with small size and light weight
- Built-in external sensitivity adjuster (Diffuse reflective type only)
- Easy to mount by screw type in mounting hole
- Built-in reverse power protection circuit and output short overcurrent protection circuit

#### Specifications

Model	BM3M-TDT	BM1M-MDT	BM200-DDT
Sensing type	Through-beam	Retroreflective	Diffuse reflective
Sensing distance	3 m	1 m <sup>01)</sup>	200 mm <sup>02)</sup>
Sensing target	Opaque materials	Opaque materials	Opaque materials, translucent materials
Min. sensing target	≥ Ø 8 mm	≥ Ø 60 mm	-
Hysteresis	-	-	≤ 10 % of sensing distance
Response time	≤ 3 ms		
Light source	Infrared		
Peak emission wavelength	940 nm		
Sensitivity adjustment	-	-	YES (Adjuster)
Operation mode	Dark ON mode	Dark ON mode	Light ON mode (option: Dark ON mode)
Indicator	Operation indicator (red)		
Approval	CE EAC	CE EAC	CE EAC
Unit weight (packaged)	≈ 170 g (≈ 240 g)	≈ 105 g (≈ 188 g)	≈ 88 g (≈ 156 g)

01) Reflector (MS-2)

02) Non-glossy white paper 200 × 200 mm

Power supply	12-24 VDC± ±10 % (ripple P-P: ≤ 10 %)
Current consumption	It depends on the sensing type
Through-beam	Emitter: ≤ 45 mA, receiver: ≤ 45 mA
Reflective	≤ 40 mA
Control output	NPN open collector output
Load voltage	≤ 30 VDC±
Load current	≤ 100 mA
Residual voltage	≤ 1.5 VDC±
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC± megger)
Noise immunity	±240 VDC± the square wave noise (pulse width: 1 μs) by the noise simulator
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx
Ambient temperature	-10 to 60 °C, storage: -25 to 70 °C (no freezing or condensation)
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)
Protection rating	-
Connection	Cable type
Cable spec.	Ø 4 mm, 3-wire, 2 m (Emitter: Ø 3 mm, 2-wire, 2 m)
Wire spec.	AWG22 (0.08 mm, 60-core), insulator outer diameter: Ø 1.25 mm
Material	Case: ABS, sensing part: PC (through-beam type) or Acrylic (retroreflective, diffuse reflective type), bracket: SPCC, bolt: SCM, nut: SCM



View product detail



# Side Sensing Photoelectric Sensors

## BMS Series



### Features

- Built-in reverse polarity protection circuit and output short overcurrent protection circuit
- Response time: Max. 1 ms
- Light ON / Dark ON mode selectable by control wire
- Sensitivity adjuster (except for through-beam type)

### Specifications

Model	BMS5M-TDT-□	BMS2M-MDT-□	BMS300-DDT-□
Sensing type	Through-beam	Retroreflective	Diffuse reflective
Sensing distance	5 m	0.1 to 2 m <sup>01)</sup>	300 mm <sup>02)</sup>
Sensing target	Opaque materials	Opaque materials	Opaque materials, translucent materials
Min. sensing target	≥ Ø 10 mm	≥ Ø 60 mm	-
Hysteresis	-	-	≤ 20 % of sensing distance
Response time	≤ 1 ms		
Light source	Infrared		
Peak emission wavelength	940 nm		
Sensitivity adjustment	-	YES (Adjuster)	YES (Adjuster)
Operation mode	Light ON mode - Dark ON mode selectable (control wire)		
Indicator	Operation indicator (red), power indicator (red) <sup>03)</sup>		
Approval	CE ENEC	CE ENEC	CE ENEC
Unit weight	≈ 180 g	≈ 110 g	≈ 100 g

01) Reflector (MS-2)

02) Non-glossy white paper 100 × 100 mm

03) Only for the emitter

Power supply	12-24 VDC±10 % (ripple P-P: ≤ 10%)
Current consumption	It depends on the sensing type
Through-beam	Emitter: ≤ 50 mA, receiver: ≤ 50 mA
Reflective	≤ 45 mA
Control output	NPN open collector output / PNP open collector output model
Load voltage	≤ 30 VDC±
Load current	≤ 200 mA
Residual voltage	NPN: ≤ 1 VDC±, PNP: ≤ 2.5 VDC±
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC± megger)
Noise immunity	±240 VDC± the square wave noise (pulse width: 1 μs) by the noise simulator
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours
Shock	500 m/s² (≈ 50 G) in each X, Y, Z direction for 3 times
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx
Ambient temperature	-10 to 60 °C, storage: -25 to 70 °C (no freezing or condensation)
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)
Protection rating	-
Connection	Cable type
Cable spec.	Ø 5 mm, 4-wire (Emitter: 2-wire), 2 m
Wire spec.	AWG22 (0.08 mm, 60-core), insulator outer diameter: Ø 1.25 mm
Material	Case: ABS, sensing part: PC (through-beam type ) or Acrylic (retroreflective, diffuse reflective type), bracket: SPCC, bolt: SCM, nut: SCM



View product detail

# Photoelectric Sensors

## with Synchronous Detection

### BY Series



#### Features

- Small size: W 12 × H 30 × L 16 mm
- Minimize malfunction by extraneous light by synchronizing emitter and receiver
- Reverse power protection circuit, output short overcurrent protection circuit
- Fast response speed: Max.1 ms

#### Specifications

Model	BY□500-TDT
Sensing type	Through-beam
Sensing distance	500 mm
Sensing target	Opaque materials
Min. sensing target	≥ Ø 5 mm
Response time	≤ 1 ms
Light source	Infrared
Peak emission wavelength	940 nm
Operation mode	Dark ON mode
Indicator	Operation indicator (red)
Approval	CE EAC
Unit weight	≈ 150 g
Power supply	12-24 VDC±10% (ripple P-P: ≤ 10%)
Current consumption	Emitter: ≤ 30 mA, receiver: ≤ 30 mA
Control output	NPN open collector output
Load voltage	≤ 30 VDC±
Load current	≤ 100 mA
Residual voltage	≤ 1 VDC±
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC± megger)
Noise immunity	±240 VDC± the square wave noise (pulse width: 1 μs) by the noise simulator
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx
Ambient temperature	-10 to 60 °C, storage: -25 to 70 °C (no freezing or condensation)
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)
Protection rating	IP50 (IEC standard)
Connection	Cable type
Cable spec.	Ø 4 mm, 4-wire (Emitter: 3-wire), 2 m
Wire spec.	AWG22 (0.08 mm, 60-core), insulator outer diameter: Ø 1.25 mm
Material	Case: ABS, sensing part: Acrylic, bracket: SPCC, bolt: SCM, nut: SCM



View product detail

# Photoelectric Sensors

## with Built-In Timer

### BYD Series



#### Features

- Easy installation by compact size
- Superior detection not affected by color of target (convergent reflective type)
- Operation indicator is located on the top (BYD30-DDT-U, BYD50-DDT-U)
- Easy to adjust the response time via timer function (OFF Delay Time: 0.1 to 2 sec)
- Reverse power protection circuit, output short overcurrent protection circuit

#### Specifications

Model	BYD3M-TDT-□	BYD100-DDT	BYD□-DDT-□
Sensing type	Through-beam	Diffuse reflective	Convergent reflective
Sensing distance	3 m	100 mm <sup>01)</sup>	10 to 30 mm ±10% <sup>01)</sup> 10 to 50 mm ±10% <sup>01)</sup>
Sensing target	Opaque materials	Opaque materials, translucent materials	Opaque materials, translucent materials
Min. sensing target	≥ Ø 6 mm	-	-
Hysteresis	-	≤ 25 % of sensing distance	≤ 10 % of sensing distance
Response time	≤ 1 ms	Operation: ≤ 3 ms Return: ≤ 100 ms	Operation: ≤ 3 ms Return: ≤ 100 ms <sup>02)</sup>
Light source	Infrared	Infrared	Infrared
Sensitivity adjustment	-	YES (Adjuster)	-
Timer function	-	-	OFF delay mode: 0.1 to 2 sec (Adjuster)
Operation mode	Dark ON mode	Light ON mode	Light ON mode
Indicator	Front	Front	Front / Upper operation indicator model
	Operation indicator (red)		
Approval	CE ENEC	CE ENEC	CE ENEC
Unit weight (packaged)	≈ 80 g (≈ 105 g)	≈ 38 g (≈ 75 g)	≈ 38 g (≈ 75 g)

01) Non-glossy white paper 50 × 50 mm

02) When the timer adjuster is set to min (0.1 sec).

Power supply	12-24 VDC±10 % (ripple P-P: ≤ 10 %)
Current consumption	It depends on the sensing type
Through-beam	Emitter: ≤ 30 mA, receiver: ≤ 30 mA
Reflective	≤ 35 mA
Control output	Through-beam type : NPN open collector output / PNP open collector output model Diffuse reflective, convergent reflective type : NPN open collector output
Load voltage	≤ 30VDC±
Load current	Through-beam type : ≤ 100 mA Diffuse reflective, convergent reflective type : ≤ 50 mA
Residual voltage	NPN: ≤ 1 VDC±, PNP: ≤ 2.5 VDC±
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC± megger)
Noise immunity	±240 VDC± the square wave noise (pulse width: 1 μs) by the noise simulator
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx
Ambient temperature	-20 to 65 °C, storage: -25 to 70 °C (no freezing or condensation)
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)
Protection rating	Through-beam, convergent reflective type (front operation indicator model) : IP64 (IEC standard), Others: IP50 (IEC standard)
Connection	Cable type
Cable spec.	Ø 3.5 mm, 3-wire (Emitter: 2-wire), 2 m
Wire spec.	AWG24 (0.08 mm, 40-core), insulator outer diameter: Ø 1 mm
Material	Case: ABS, sensing part: Acrylic, bracket: SPCC, bolt: SCM, nut: SCM, sleeve: Brass, Ni-plate



View product detail

# Front / Side Mount

## Photoelectric

## Sensors

### BH Series



#### Features

- Easy front (M18 nut) and side (M3 bolt/nut) installation
- NPN open collector / PNP open collector simultaneous output
- Sensing distance:  
Through-beam type 20 m /  
Polarized retroreflective type 4 m /  
Diffuse reflective type 1 m, 300 mm
- Small size: W 14 × H 34.5 × L 28 mm
- M.S.R. (Mirror Surface Rejection) function prevents malfunction from reflective objects such as metals or mirrors (polarized retroreflective type)
- Built-in sensitivity adjuster
- Light ON / Dark ON selectable by switch
- Operation indicator (red), stability indicator (green)
- Reverse power protection circuit, output short overcurrent protection circuit
- Mutual interference prevention function (except through-beam type)
- IP67 protection rating (IEC standard)



View product detail

#### Specifications

Model	BH20M-TDT	BH4M-PDT	BH□-DDT	
Sensing type	Through-beam	Polarized retroreflective	Diffuse reflective	
Sensing distance	20 m	4 m <sup>01)</sup>	300 mm <sup>02)</sup>	1 m <sup>03)</sup>
Sensing target	Opaque materials	Opaque materials	-	
Min. sensing target	≥ Ø 20 mm	≥ Ø 75 mm	-	
Hysteresis	-	-	≤ 20 % of sensing distance	
Response time	≤ 1 ms			
Light source	Red	Red	Red	Infrared
Peak emission wavelength	660 nm	660 nm	660 nm	850 nm
Sensitivity adjustment	YES (Adjuster)	YES (Adjuster)	YES (Adjuster)	
Mutual interference prevention	-	YES	YES	
Operation mode	Light ON mode - Dark ON mode selectable (Adjuster)			
Indicator	Operation indicator (red), stability indicator (green), power Indicator (green) <sup>04)</sup>			
Approval	CE  ENEC	CE  ENEC	CE  ENEC	
Unit weight (packaged)	≈ 120 g (≈ 190 g)	≈ 60 g (≈ 140 g)	≈ 60 g (≈ 130 g)	

01) Reflector (MS-2A)

02) Non-glossy white paper 100 × 100 mm

03) Non-glossy white paper 300 × 300 mm

04) Only for the emitter

Power supply	12-24 VDC±10 % (ripple P-P: ≤ 10%)
Current consumption	It depends on the sensing type
Through-beam	Emitter: ≤ 20 mA, receiver : ≤ 20 mA
Polarized retroreflective	≤ 30 mA
Diffuse reflective (300 mm)	≤ 30 mA
Diffuse reflective (1 m)	≤ 35 mA
Control output	NPN open collector - PNP open collector simultaneous output
Load voltage	≤ 26.4 VDC±
Load current	≤ 100 mA
Residual voltage	NPN: ≤ 1 VDC±, PNP: ≤ 2.5 VDC±
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC± megger)
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx
Ambient temperature	-25 to 55 °C, storage: -40 to 70 °C <sup>01)</sup> (no freezing or condensation)
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)
Protection rating	IP67 (IEC standard)
Connection	Cable type
Cable spec.	Ø 4 mm, 4-wire (Emitter: 2-wire), 2.1 m
Wire spec.	AWG24 (0.08 mm, 40-core), insulator outer diameter: Ø 1.03 mm
Material	Case: PC, CAP: PC, sensing part: PMMA

01) UL approved ambient temperature 40°C

# Diffuse Reflective Long-Distance Photoelectric Sensors

## BA Series



### Features

- Realization of long sensing distance (2 m) by special optical design
- Built-in stability indicator
- Sensitivity adjustment function
- 2 color display
- IP64 protection rating (IEC standard)

### Specifications

Model	BA2M-DDT□-□
Sensing type	Diffuse reflective
Sensing distance	2 m <sup>01)</sup>
Sensing target	Opaque materials, translucent materials
Hysteresis	≤ 20 % of sensing distance
Response time	≤ 1 ms
Light source	Infrared
Peak emission wavelength	850 nm
Sensitivity adjustment	YES (Adjuster)
Operation mode	Light ON mode / Dark ON mode model
Indicator	Operation indicator (red), stability indicator (Light ON: orange, Dark ON: green)
Approval	CE ENEC
Unit weight	≈ 50 g

01) Non-glossy white paper 200 × 200 mm

Power supply	12-24 VDC≡ ±10 % (ripple P-P: ≤ 10%)
Current consumption	≤ 15 mA (output ON: ≤ 30 mA)
Control output	NPN open collector output / PNP open collector output model
Load voltage	≤ 26.4 VDC≡
Load current	≤ 100 mA
Residual voltage	NPN: ≤ 1 VDC≡, PNP: ≤ 2.5 VDC≡
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC≡ megger)
Noise immunity	±240 VDC≡ the square wave noise (pulse width: 1 μs) by the noise simulator
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours
Shock	100 m/s <sup>2</sup> (≈ 10 G) in each X, Y, Z direction for 3 times
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx
Ambient temperature	-25 to 55 °C, storage: -25 to 70 °C (no freezing or condensation)
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)
Protection rating	IP64 (IEC standard)
Connection	Cable type
Cable spec.	Ø 3 mm, 3-wire, 2 m
Wire spec.	AWG24 (0.08 mm, 40-core), insulator outer diameter: Ø 1 mm
Material	Case: ABS, CAP: PC, sensing part: PC, adjuster: IXEF



View product detail

# L 3.7 mm Flat

## Photoelectric

## Sensors

### BTF Series



#### Features

- Ultra-thin size of only 3.7 mm
  - W 13 × H 19 × L 3.7 mm (Through-beam type)
  - W 13 × H 24 × L 3.7 mm (Diffuse reflective type, BGS reflective type)
- Detection methods and minimum target size
  - Through-beam type (BTF1M): Ø 2 mm
  - Diffuse reflective type (BTF30): Ø 0.2 mm (sensing distance: 10 mm)
  - BGS reflective type (BTF15): Ø 0.2 mm (sensing distance: 10 mm)
- BGS (background suppression) minimizes detection errors from background objects and the color or material of target objects.
- Maximum sensing distance: 1 m (Through-beam type)
- Operation indicator (red) and stability indicator (green) show operation status
- Stainless steel (SUS304) mounting brackets
- IP67 protection rating (IEC standard)

#### Specifications

Model	BTF1M-TDT□-□	BTF30-DDT□-□	BTF15-BDT□-□
Sensing type	Through-beam	Diffuse reflective	BGS reflective
Sensing distance	1 m	5 to 30 mm <sup>01)</sup>	1 to 15 mm <sup>01)</sup>
Sensing target	Opaque materials	Opaque materials, translucent materials	Opaque materials, translucent materials
Min. sensing target	≥ Ø 2 mm	≥ Ø 0.2 mm <sup>02)</sup>	≥ Ø 0.2 mm non-illuminated objects <sup>02)</sup>
Hysteresis	-	≤ 20% of sensing distance	≤ 5% of sensing distance
Black/white difference	-	-	≤ 15% of sensing distance
Response time	≤ 1 ms		
Light source	Red		
Peak emission wavelength	650 nm		
Operation mode	Light ON mode / Dark ON mode model		
Indicator	Operation indicator (red), stability indicator (green)		
Approval	CE EAC	CE EAC	CE EAC
Unit weight (packaged)	≈ 40 g (≈ 70 g)	≈ 25 g (≈ 40 g)	≈ 25 g (≈ 40 g)

01) Non-glossy white paper 50 × 50 mm

02) Sensing distance 10 mm

Power supply	12-24 VDC≡ ±10 % (ripple P-P: ≤ 10%)
Current consumption	It depends on the sensing type
Through-beam	Emitter: ≤ 20 mA, receiver: ≤ 20 mA
Reflective	≤ 20 mA
Control output	NPN open collector output / PNP open collector output model
Load voltage	≤ 26.4 VDC≡
Load current	≤ 50 mA
Residual voltage	NPN: ≤ 1 VDC≡, PNP: ≤ 2 VDC≡
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC≡ megger)
Noise immunity	±240 VDC≡ the square wave noise (pulse width: 1 μs) by the noise simulator
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times
Ambient illuminance (receiver)	Sunlight: ≤ 10,000 lx, incandescent lamp: ≤ 3,000 lx
Ambient temperature	-25 to 55 °C, storage: -40 to 70 °C (no freezing or condensation)
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)
Protection rating	IP67 (IEC standard)
Connection	Cable type
Cable spec.	Ø 2.5 mm, 3-wire (emitter: 2-wire), 2 m
Wire spec.	AWG 28 (0.08 mm, 19-core), insulator outer diameter: Ø 0.9 mm
Material	Case: PBT, sensing part: PMMA, bracket: SUS304, bolt: carbon steel, sleeve: SUS304



View product detail

# L 7.5 mm Flat

## Photoelectric

### Sensors

#### BPS Series



#### Features

- Easy to mount by flat type
- Realization of 3m sensing distance as small size
- IP67 protection rating (IEC standard)

#### Specifications

Model	BPS3M-TDT□-□
Sensing type	Through-beam
Sensing distance	3 m
Sensing target	Opaque materials
Min. sensing target	≥ Ø 5 mm
Response time	≤ 1 ms
Light source	Infrared
Peak emission wavelength	850 nm
Operation mode	Light ON mode / Dark ON mode model
Indicator	Power Indicator of emitter (red), operation indicator of receiver (red)
Approval	CE ENEC
Unit weight	≈ 66 g
Power supply	12-24 VDC≐ ±10 % (ripple P-P: ≤ 10 %)
Current consumption	Emitter: ≤ 20 mA, receiver: ≤ 20 mA
Control output	NPN open collector output / PNP open collector output model
Load voltage	≤ 30 VDC≐
Load current	≤ 100 mA
Residual voltage	NPN: ≤ 1 VDC≐, PNP: ≤ 2.5 VDC≐
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC≐ megger)
Noise immunity	±240 VDC≐ the square wave noise (pulse width: 1 μs) by the noise simulator
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx
Ambient temperature	-25 to 65 °C, storage: -25 to 70 °C (no freezing or condensation)
Ambient humidity	35 to 85 %RH, storage: 35 to 90 %RH (no freezing or condensation)
Protection rating	IP67 (IEC standard)
Connection	Cable type
Cable spec.	Ø 3 mm, 3-wire (Emitter: 2-wire), 2 m
Wire spec.	AWG24 (0.08 mm, 40-core), insulator outer diameter: Ø 1 mm
Material	Case: PC, bolt: SCM, nut: SCM



View product detail

# Cylindrical Photoelectric Sensors (Front Sensing Type)

## BRQ Series



### Features

- Excellent noise immunity and minimal influence from ambient light
- Reverse power protection circuit, reverse output protection circuit, output short overcurrent protection circuit
- Mutual interference prevention function (except through-beam type)
- Sensitivity adjuster
- Light ON / Dark ON mode selectable by control wire
- Various materials:  
Plastic, Metal (Ni-plated Brass), SUS316L
- Long sensing distance:  
30 m (through-beam type)
- Body size
  - BRQT, BRQM: Standard
  - BRQP: Standard, Short body
- Protection rating
  - BRQT: IP67 (IEC standard), IP69K (DIN standard)
  - BRQM, BRQP: IP67 (IEC standard)



View product detail

### Specifications

Model	BRQ□□-TDT□-□-□	BRQ□3M-PDT□-□-□	BRQ□□-DDT□-□-□
Sensing type	Through-beam	Polarized retroreflective	Diffuse reflective
Sensing distance	5 m    20 m    30 m	3 m <sup>01)</sup>	100 mm <sup>02)</sup> 400 mm <sup>02)</sup> 1 m <sup>03)</sup>
Sensing target	Opaque materials	Opaque materials	Opaque, translucent materials
Min. sensing target	≥ Ø 7 mm	≥ Ø 75 mm	-
Hysteresis	-	-	≤ 20 % of sensing distance
Response time	≤ 1 ms		
Light source	Red	Red	Infrared    Red    Red
Peak emission wavelength	660 nm	660 nm	850 nm    660 nm    660 nm
Sensitivity adjustment	YES (Adjuster)	YES (Adjuster)	YES (Adjuster)
Mutual interference prevention	-	YES	YES
Operation mode	Light ON mode - Dark ON mode selectable (Control wire)		
Indicator	Operation indicator (yellow), stability indicator (green), power indicator (red) <sup>04)</sup>		
Approval	CE  ENEC	CE  ENEC	CE  ENEC

01) Reflector (MS-2A)

02) Non-glossy white paper 100 × 100 mm

03) Non-glossy white paper 300 × 300 mm

04) Only for the emitter

Unit weight (packaged)	Material	Through-beam	Polarized retroreflective, Diffuse reflective
Cable type	SUS316L	≈ 140 g (≈ 220 g)	≈ 70 g (≈ 150 g)
	Brass, Ni-plate	≈ 140 g (≈ 220 g)	≈ 70 g (≈ 150 g)
	Plastic	≈ 110 g (≈ 160 g)	≈ 60 g (≈ 120 g)
	Plastic (short)	≈ 100 g (≈ 150 g)	≈ 50 g (≈ 120 g)
Connector type	SUS316L	≈ 50 g (≈ 160 g)	≈ 30 g (≈ 140 g)
	Brass, Ni-plate	≈ 50 g (≈ 160 g)	≈ 30 g (≈ 140 g)
	Plastic	≈ 25 g (≈ 110 g)	≈ 15 g (≈ 110 g)
	Plastic (short)	≈ 20 g (≈ 100 g)	≈ 10 g (≈ 100 g)

Power supply	10-30 VDC≡ ±10 % (ripple P-P: ≤ 10 %)
Current consumption	It depends on the sensing type
Through-beam	Emitter: ≤ 20 mA, receiver: ≤ 20 mA
Reflective	≤ 30 mA
Control output	NPN open collector output / PNP open collector output model
Load voltage	≤ 30 VDC≡
Load current	≤ 100 mA
Residual voltage	NPN: ≤ 2 VDC≡, PNP: ≤ 2 VDC≡
Protection circuit	Reverse power/output protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC≡ megger)
Noise immunity	±240 VDC≡ the square wave noise (pulse width: 1 μs) by the noise simulator
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx
Ambient temperature	-25 to 60 °C, storage: -30 to 70 °C (no freezing or condensation)
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)
Protection rating	IP67 (IEC standard), SUS316L material model: IP67 (IEC standard), IP69K (DIN standard)
Connection	Cable type / Connector type model
Cable spec.	Ø 4 mm, 4-wire, (Emitter: 2-wire), 2 m
Wire spec.	AWG26 (0.52 mm, 20-core), insulator outer diameter: Ø 1 mm
Connector	M12 4-pin plug type
Material	Case: It depends on the model. (refer to 'Ordering Information'), lens and lens cover: PMMA



# Cylindrical Photoelectric Sensors

(Side Sensing Type)

## BRQ Series



### Features

- Excellent noise immunity and minimal influence from ambient light
- Reverse power protection circuit, reverse output protection circuit, output short overcurrent protection circuit
- Mutual interference prevention function (except through-beam type)
- Sensitivity adjuster
- Light ON / Dark ON mode selectable by control wire
- Protection rating: IP67 (IEC standard)

### Specifications

Model	BRQPS□-TDTA-□-□	BRQPS3M-PDTA-□-□	BRQPS□-DDTA-□-□
Sensing type	Through-beam	Polarized retroreflective	Diffuse reflective
Sensing distance	10 m      20 m	3 m <sup>01)</sup>	100 mm <sup>02)</sup> 400 mm <sup>02)</sup> 700 mm <sup>03)</sup>
Sensing target	Opaque materials	Opaque materials	Opaque, translucent materials
Min. sensing target	≥ Ø 7 mm	≥ Ø 75 mm	-
Hysteresis	-	-	≤ 20 % of sensing distance
Response time	≤ 1 ms		
Light source	Red	Red	Red
Peak emission wavelength	660 nm	660 nm	660 nm
Sensitivity adjustment	YES (Adjuster)	YES (Adjuster)	YES (Adjuster)
Mutual interference prevention	-	YES	YES
Operation mode	Light ON mode - Dark ON mode selectable (Control wire)		
Indicator	Operation indicator (yellow), stability indicator (green), power indicator (red) <sup>04)</sup>		
Approval	CE c  ENEC	CE c  ENEC	CE c  ENEC

01) Reflector (MS-2S)

02) Non-glossy white paper 100 × 100 mm

03) Non-glossy white paper 200 × 200 mm

04) Only for the emitter

Unit weight (packaged)	Through-beam	Polarized retroreflective, Diffuse reflective
Cable type	≈ 120 g (≈ 170 g)	≈ 70 g (≈ 130 g)
Connector type	≈ 35 g (≈ 120 g)	≈ 25 g (≈ 120 g)
Power supply	10-30 VDC≡ ±10 % (ripple P-P: ≤ 10 %)	
Current consumption	It depends on the sensing type	
Through-beam	Emitter: ≤ 20 mA, receiver: ≤ 20 mA	
Reflective	≤ 30 mA	
Control output	NPN open collector output / PNP open collector output model	
Load voltage	≤ 30 VDC≡	
Load current	≤ 100 mA	
Residual voltage	NPN: ≤ 2 VDC≡, PNP: ≤ 2 VDC≡	
Protection circuit	Reverse power/output protection circuit, output short overcurrent protection circuit	
Insulation resistance	≥ 20 MΩ (500 VDC≡ megger)	
Noise immunity	±240 VDC≡ the square wave noise (pulse width: 1 μs) by the noise simulator	
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min	
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours	
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times	
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx	
Ambient temperature	-25 to 60 °C, storage: -30 to 70 °C (no freezing or condensation)	
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)	
Protection rating	IP67 (IEC standard)	
Connection	Cable type / Connector type model	
Cable spec.	Ø 4 mm, 4-wire, (Emitter: 2-wire), 2 m	
Wire spec.	AWG26 (0.52 mm, 20-core), insulator outer diameter: Ø 1 mm	
Connector	M12 4-pin plug type	
Material	Case: PC, lens and lens cover: PMMA	



View product detail

# Cylindrical Photoelectric Sensors

## BR Series



### Features

- Superior noise resistance with digital signal processing
- High-speed response time under 1 ms
- Built-in reverse power protection circuit and output short overcurrent protection circuit
- Suitable for sensing in narrow space (narrow beam type)
- External sensitivity adjustment
- Light ON / Dark ON mode selectable by control wire
- IP66 protection rating (IEC standard)

### Specifications

Model	BR□200-DDTN-□-□
Sensing type	Narrow beam reflective
Sensing distance	200 mm <sup>01)</sup>
Sensing target	Opaque materials, translucent materials
Hysteresis	≤ 20 % of sensing distance
Response time	≤ 1 ms
Light source	Infrared
Peak emission wavelength	850 nm
Sensitivity adjustment	YES (Adjuster)
Operation mode	Light ON mode - Dark ON mode selectable (Control wire)
Indicator	Operation indicator (red)
Approval	CE ENEC

01) Non-glossy white paper 100 × 100 mm

Unit weight (packaged)	Metal material model	Plastic material model
Cable type	≈ 120 g (≈ 160 g)	≈ 100 g (≈ 140 g)
Connector type	≈ 50 g (≈ 90 g)	≈ 30 g (≈ 70 g)
Power supply	12-24 VDC≒ ±10 % (ripple P-P: ≤ 10 %)	
Current consumption	≤ 45 mA	
Control output	NPN open collector output / PNP open collector output model	
Load voltage	≤ 30 VDC≒	
Load current	≤ 200 mA	
Residual voltage	NPN: ≤ 1 VDC≒, PNP: ≤ 2.5 VDC≒	
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit	
Insulation resistance	≥ 20 MΩ (500 VDC≒ megger)	
Noise immunity	±240 VDC≒ the square wave noise (pulse width: 1 μs) by the noise simulator	
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min	
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours	
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times	
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx	
Ambient temperature	-10 to 60 °C, storage: -25 to 75 °C (no freezing or condensation)	
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)	
Protection rating	IP66 (IEC standard)	
Connection	Cable type / Connector type model	
Cable spec.	Ø 5 mm, 4-wire, 2 m	
Wire spec.	AWG22 (0.08 mm, 60-core), insulator outer diameter: Ø 1.25 mm	
Connector	M12 4-pin plug type	
Material	Case: Brass, Ni-plate (metal material model) or PA Black (plastic material model), sensing part: PC lens	



View product detail

# 4-Channel U-Shaped Photoelectric Sensors

## BUM Series



### Features

- Highly reliable 4 channel detection
- High-speed response time under 1 ms
- Built-in reverse power protection circuit and output short overcurrent protection circuit
- IP65 protection rating (IEC standard)

### Specifications

Model	BUM4-40D-W-4M	BUM4-40D-W-□/A	BUM4-40D-W-□/B
Sensing type	Through-beam		
Sensing distance	40 mm		
Sensing target	Opaque materials		
Min. sensing target	≥ Ø 4 mm		
Response time	≤ 1 ms		
Light source	Infrared		
Peak emission wavelength	940 nm		
Operation mode	Dark ON mode		
Indicator	Output Indicator (red), power indicator (green)		
Approval	CE ENEC		
Unit weight (packaged)	≈ 500 g (≈ 510 g)	≈ 500 g (≈ 1.5 kg)	≈ 500 g (≈ 1.5 kg)
Power supply	18-35 VDC≡ ±10 % (ripple P-P: ≤ 10%)		
Current consumption	≤ 50 mA		
Control output	NPN open collector output (individual 4 output)		
Load voltage	≤ 35 VDC≡		
Load current	≤ 100 mA		
Residual voltage	≤ 4 VDC≡		
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit		
Insulation resistance	≥ 20 MΩ (500 VDC≡ megger)		
Noise immunity	±240 VDC≡ the square wave noise (pulse width: 1 μs) by the noise simulator		
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min		
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours		
Shock	500 m/s² (≈ 50 G) in each X, Y, Z direction for 3 times		
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx		
Ambient temperature	-25 to 65 °C, storage: -25 to 70 °C (no freezing or condensation)		
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)		
Protection rating	IP65 (IEC standard)		
Connection	Cable type		
Cable spec.	Ø 6 mm, 8-wire, 2 m / 3 m / 4 m model		
Wire spec.	AWG22 (1.2 mm, 60-core)		
Material	Case, cover: ABS		



View product detail

# 1-Channel U-Shaped Photoelectric Sensors

## BUP Series



### Features

- Various sensing distance's lineup:  
30 mm, 50 mm models
- High speed response type: Max. 1 ms
- Offers the sensitivity adjustable model
- Light ON / Dark ON operation mode  
selectable by control wire

### Specifications

Model	BUP-□-□		BUP-□-E		BUP-□S-□	
Sensing type	Through-beam					
Sensing distance	30 mm	50 mm	30 mm	50 mm	30 mm	50 mm
Sensing target	Opaque materials					
Min. sensing target	≥ Ø 4 mm				≥ Ø 1.5 mm	
Response time	≤ 1 ms					
Light source	Infrared					
Peak emission wavelength	940 nm					
Sensitivity adjustment	Fixed				YES (Adjuster)	
Operation mode	Light ON mode - Dark ON mode selectable (Control wire)					
Indicator	Operation indicator (red), power indicator (green)					
Approval	CE ENEC		CE		CE ENEC	
Unit weight (packaged)	≈ 85 g (≈ 120 g)	≈ 115 g (≈ 160 g)	≈ 60 g (≈ 95 g)	≈ 90 g (≈ 125 g)	≈ 85 g (≈ 120 g)	≈ 115 g (≈ 160 g)
Power supply	12-24 VDC≒ ±10 % (ripple P-P: ≤ 10%)					
Current consumption	≤ 30 mA					
Control output	NPN open collector output / PNP open collector output model					
Load voltage	≤ 30 VDC≒					
Load current	≤ 200 mA					
Residual voltage	NPN: ≤ 1 VDC≒, PNP: ≤ 2.5 VDC≒					
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit					
Insulation resistance	≥ 20 MΩ (500 VDC≒ megger)					
Noise immunity	±240 VDC≒ the square wave noise (pulse width: 1 μs) by the noise simulator					
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min					
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours					
Shock	500 m/s² (≈ 50 G) in each X, Y, Z direction for 3 times					
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx					
Ambient temperature	Fixed sensitivity model: -25 to 65 °C, storage: -25 to 70 °C (no freezing or condensation) Sensitivity adjustable model: -10 to 60 °C, storage: -25 to 70 °C (no freezing or condensation)					
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)					
Protection rating	Fixed sensitivity model: IP66 (IEC standard) Sensitivity adjustable model: IP50 (IEC standard)					
Connection	Cable type, cable connector type					
Cable spec.	Cable type: Ø 4 mm, 4-wire, 2 m Cable connector type: Ø 4 mm, 4-wire, 0.5 m					
Wire spec.	AWG22 (0.08 mm, 60-core), insulator outer diameter: Ø 1.25 mm					
Connector	5-pin socket type					
Material	Case: ABS, CAP: PC					



View product detail

# Universal AC / DC

## Photoelectric

### Sensors

#### BEN Series



#### Features

- Small and power supply built-in type
- Easy installation with indicators on product
- Light ON / Dark ON mode selectable by switch
- Status and output indication
- Built-in IC photo diode for disturbing light and electrical noise

#### Specifications

Model	BEN10M-T <input type="checkbox"/>	BEN5M-M <input type="checkbox"/>	BEN3M-P <input type="checkbox"/>	BEN300-D <input type="checkbox"/>
Sensing type	Through-beam	Retroreflective	Polarized retroreflective	Diffuse reflective
Sensing distance	10 m	0.1 to 5 m <sup>01)</sup>	0.1 to 3 m <sup>01)</sup>	300 mm <sup>02)</sup>
Sensing target	Opaque materials	Opaque materials	Opaque materials	Opaque, translucent materials
Min. sensing target	≥ Ø 16 mm	≥ Ø 60 mm	≥ Ø 60 mm	-
Hysteresis	-	-	-	≤ 20 % of sensing distance
Response time	AC/DC power, relay contact output model: ≤ 20 ms DC power, solid state (transistor) output model: ≤ 1 ms			
Light source	Infrared	Infrared	Red	Infrared
Peak emission wavelength	850 nm	940 nm	660 nm	940 nm
Sensitivity adjustment	-	YES (Adjuster)	YES (Adjuster)	YES (Adjuster)
Operation mode	Light ON mode - Dark ON mode selectable (Adjuster)			
Indicator	Operation indicator (red), stability indicator (green), power indicator (red) <sup>03)</sup>			
Approval	CE [REDACTED]			
Unit weight (AC/DC power)	≈ 354 g	≈ 208 g	≈ 208 g	≈ 195 g
Unit weight (DC power)	≈ 342 g	≈ 200 g	≈ 200 g	≈ 187 g

01) Reflector (MS-2)

02) Non-glossy white paper 100 × 100 mm

03) Only for the emitter

Output method	AC/DC power, relay contact output	DC power, solid state (transistor) output
Power supply	24-240 VAC ~ ± 10 % 50/60 Hz 24-240 VDC = ± 10 % (ripple P-P: ≤ 10 %)	12-24 VDC = ± 10 % (ripple P-P: ≤ 10 %)
Power / current consumption	≤ 4 VA	It depends on the sensing type
Through-beam	-	Emitter: ≤ 50 mA, receiver: ≤ 50 mA
Reflective	-	≤ 50 mA
Control output	Relay contact output	NPN open collector - PNP open collector simultaneous output
Contact capacity	250 VAC ~ 3 A of resistance load, 30 VDC = 3 A of resistance load	-
Contact composition	1c	-
Relay life cycle	Mechanical: ≥ 50,000,000 Electrical: ≥ 100,000	-
Load voltage	-	≤ 30 VDC =
Load current	-	≤ 200 mA
Residual voltage	-	NPN: ≤ 1 VDC =, PNP: ≤ 2.5 VDC =
Protection circuit	-	Reverse power protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC = megger)	-
Insulation type	Double or strong insulation (dielectric voltage between the measured input and the power : 1 kV)	-
Noise immunity	± 1,000 VDC = the square wave noise (pulse width: 1 μs) by the noise simulator	± 240 VDC = the square wave noise (pulse width: 1 μs) by the noise simulator



View product detail

<b>Dielectric strength</b>	1,000 VAC~ 50/60 Hz for 1 min	
<b>Vibration</b>	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours	
<b>Vibration (malfunction)</b>	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 10 min	-
<b>Shock</b>	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times	
<b>Shock (malfunction)</b>	100 m/s <sup>2</sup> (≈ 10 G) in each X, Y, Z direction for 3 times	-
<b>Ambient illuminance (receiver)</b>	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx	
<b>Ambient temperature</b>	-20 to 65 °C, storage: -20 to 70 °C (no freezing or condensation)	
<b>Ambient humidity</b>	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)	
<b>Protection rating</b>	IP50 (IEC standard)	
<b>Connection</b>	Cable type	
<b>Cable spec.</b>	Ø 5 mm, Emitter: 2-wire, AC/DC power: 5-wire, DC power: 4-wire, 2 m	
<b>Wire spec.</b>	AWG22 (0.08 mm, 60-core), insulator outer diameter: Ø 1.25 mm	
<b>Material</b>	Case and case cover: heat resistant ABS, sensing part: PC (polarized retroreflective: PMMA)	

# Universal AC / DC

## Photoelectric

## Sensors

### BX Series



#### Features

- Built-in sensitivity adjuster
- Timer function (built-in timer model)
  - ON Delay, OFF Delay, One-shot Delay
- NPN / PNP open collector simultaneous output (DC power Type)
- Self-diagnosis function  
(green lights up in the stable level)
- Built-in reverse power protection circuit and output short overcurrent protection circuit
- Wide power supply range:  
Universal 24-240 VDC $\equiv$  / 24-240 VAC $\sim$
- IP66 protection rating (IEC standard)

#### Specifications

Model	BX15M-T□-□	BX5M-M□-□	BX3M-P□-□	BX700-D□-□
Sensing type	Through-beam	Retroreflective	Polarized retroreflective	Diffuse reflective
Sensing distance	15 m	0.1 to 5 m <sup>01)</sup>	0.1 to 3 m <sup>02)</sup>	700 mm <sup>03)</sup>
Sensing target	Opaque materials	Opaque materials	Opaque materials	Opaque, translucent materials
Min. sensing target	≥ Ø 15 mm	≥ Ø 60 mm	≥ Ø 60 mm	-
Hysteresis	-	-	-	≤ 20 % of sensing distance
Response time	AC/DC power, relay contact output model: ≤ 20 ms DC power, solid state (transistor) output model: ≤ 1 ms			
Light source	Infrared	Infrared	Red	Infrared
Peak emission wavelength	850 nm	940 nm	660 nm	940 nm
Sensitivity adjustment	YES (Adjuster)	YES (Adjuster)	YES (Adjuster)	YES (Adjuster)
Timer mode <sup>04)</sup>	OFF, ON Delay, OFF Delay, One Shot Delay mode selectable (Switch): 0.1 to 5 sec (Adjuster)			
Operation mode	Light ON mode - Dark ON mode selectable (Switch)			
Indicator	Operation indicator (yellow), self-diagnosis indicator (green), power indicator (yellow) <sup>05)</sup>			
Approval	CE ENEC	CE ENEC	CE ENEC	CE ENEC
Unit weight	Based on the standard model, timer model: weight + 1 g			
AC/DC power	≈ 225 g	≈ 130 g	≈ 148 g	≈ 115 g
DC power	≈ 211 g	≈ 123 g	≈ 141 g	≈ 116 g

01) Reflector (MS-2)

02) Reflector (MS-3)

03) Non-glossy white paper 200 × 200 mm

04) Only for the timer model

05) Only for the emitter

Output method	AC/DC power, relay contact output	DC power, Transistor solid state output
Power supply	24-240 VAC $\sim$ ± 10 % 50/60 Hz 24-240 VDC $\equiv$ ± 10 % (ripple P-P: ≤ 10 %)	12-24 VDC $\equiv$ ± 10 % (ripple P-P: ≤ 10 %)
Power / current consumption	≤ 3 VA	It depends on the sensing type
Through-beam		Emitter: ≤ 50 mA, receiver: ≤ 50 mA
Reflective		≤ 50 mA
Control output	Relay contact output	NPN open collector - PNP open collector simultaneous output
Contact capacity	250 VAC $\sim$ 3 A of resistance load, 30 VDC $\equiv$ 3 A of resistance load	-
Contact composition	1c	
Relay life cycle	Mechanical: ≥ 50,000,000 Electrical: ≥ 100,000	
Load voltage	-	≤ 30 VDC $\equiv$
Load current		≤ 200 mA
Residual voltage		NPN: ≤ 1 VDC $\equiv$ , PNP: ≤ 2.5 VDC $\equiv$
Self-diagnosis output	-	NPN open collector output <sup>01)</sup>
Protection circuit	-	Reverse power protection circuit, output short overcurrent protection circuit

01) Load voltage: ≤ 30 VDC $\equiv$ , load current: ≤ 50 mA, residual voltage: ≤ 1 VDC $\equiv$  (50 mA), ≤ 0.4 VDC $\equiv$  (16 mA)



View product detail

<b>Insulation resistance</b>	≥ 20 MΩ (500 VDC≡ megger)	
<b>Insulation type</b>	Double or strong insulation (dielectric voltage between the measured input and the power : 1.5 kV)	-
<b>Noise immunity</b>	± 1,000 VDC≡ the square wave noise (pulse width: 1 μs) by the noise simulator	±240 VDC≡ the square wave noise (pulse width: 1 μs) by the noise simulator
<b>Dielectric strength</b>	1,500 VAC~ 50/60 Hz for 1 min	
<b>Vibration</b>	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours	
<b>Vibration (malfunction)</b>	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 10 min	
<b>Shock</b>	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times	
<b>Shock (malfunction)</b>	100 m/s <sup>2</sup> (≈ 10 G) in each X, Y, Z direction for 3 times	
<b>Ambient illuminance (receiver)</b>	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx	
<b>Ambient temperature</b>	-20 to 55 °C, storage: -25 to 70 °C (no freezing or condensation)	
<b>Ambient humidity</b>	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)	
<b>Protection rating</b>	IP66 (IEC standard)	
<b>Connection</b>	Terminal type	
<b>Material</b>	Case, lens cover: PC, sensing part: Acrylic, bracket: SPCC, bolt: SCM, nut: SCM	



# Photoelectric Sensors

## for PCB Detection

### BJP Series



#### Features

- 30 mm × 3 mm of rectangular light beam (at 30 mm distance) provides accurate detection of PCBs regardless of holes, incomplete fabrication, protrusions, or intrusions on the boards.
- Background suppression (BGS) sensing method allows stable detection regardless of the color, texture or surface of the background object.
- Sensing distance: 10 to 100 mm (adjustable distance: 20 to 100 mm)
- Switch for selecting Light ON / Dark ON mode
- Reverse power protection circuit, output short overcurrent protection circuit
- IP65 protection rating (IEC standard)

#### Specifications

Model	BJP100-BDT-□
Sensing type	BGS reflective
Sensing distance	10 to 100 mm <sup>01)</sup> (at sensing distance: 100 mm)
Sensing target	Opaque materials
Sensing distance setting	20 to 100 mm <sup>01)</sup>
Hysteresis	≤ 10 % of setting distance <sup>01)</sup>
Response time	≤ 1.5 ms
Light source	Red
Peak emission wavelength	660 nm
Beam spot size	W 3 × L 30 mm (at sensing distance: 30 mm)
Operation mode	Light ON mode - Dark ON mode selectable (Adjuster)
Indicator	Operation indicator (red), stability indicator (green)
Approval	CE ENEC
Unit weight (packaged)	≈ 50 g (≈ 105 g)

<sup>01)</sup> Non-glossy white paper 100 × 100 mm

Power supply	12-24 VDC≒ ±10 % (ripple P-P: ≤ 10 %)
Current consumption	≤ 30 mA
Control output	NPN open collector output / PNP open collector output model
Load voltage	≤ 26.4 VDC≒
Load current	≤ 100 mA
Residual voltage	NPN: ≤ 1 VDC≒, PNP: ≤ 2 VDC≒
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC≒ megger)
Noise immunity	±240 VDC≒ the square wave noise (pulse width: 1 μs) by the noise simulator
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times
Ambient illuminance (receiver)	Sunlight: ≤ 10,000 lx, incandescent lamp: ≤ 3,000 lx
Ambient temperature	-25 to 55 °C, storage: -40 to 70°C (no freezing or condensation)
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)
Protection rating	IP65 (IEC standard)
Connection	Cable type
Cable spec.	Ø 3.5 mm, 3-wire, 2 m
Wire spec.	AWG24 (0.08 mm, 40-core), insulator outer diameter: Ø 1 mm
Material	Case: PC+ABS, CAP: PC, sensing part: PMMA



View product detail

# Oil-Resistant Photoelectric Sensors

## BJR Series



### Features

- Long sensing distance with lens of high performance: Through-beam type 15 m, diffuse reflective type 1 m, polarized retroreflective type 3 m (MS-2S)
- M.S.R. (Mirror Surface Rejection) function (Polarized retroreflective type)
- Compact size: W 11 × H 32 × L 20 mm
- Light ON / Dark ON operation mode switch
- Built-in sensitivity adjustment adjuster
- Reverse power protection circuit and output short overcurrent protection circuit
- Mutual interference prevention function (except through-beam type)
- Excellent noise immunity and minimal influence from ambient light
- Stronger in the environment with full of cutting fluid or lubricating oil (optimized for automobile and machine tool industry)
- IP67 protection rating (IEC standard), IP67G oil resistance protection rating (JEM standard)



View product detail

### Specifications

Model	BJR15M-TDT-□-□	BJR3M-PDT-□-□	BJR□-DDT-□-□	
Sensing type	Through-beam	Polarized retroreflective	Diffuse reflective	
Sensing distance	15 m	3 m <sup>01)</sup>	100 mm <sup>02)</sup>	1 m <sup>03)</sup>
Sensing target	Opaque materials	Opaque materials	Opaque materials, translucent materials	
Min. sensing target	≥ Ø 12 mm	≥ Ø 75 mm	-	-
Hysteresis	-	-	≤ 20 % of sensing distance	
Response time	≤ 1 ms			
Light source	Infrared	Red	Infrared	Red
Peak emission wavelength	850 nm	660 nm	850 nm	660 nm
Sensitivity adjustment	YES (Adjuster)	YES (Adjuster)	YES (Adjuster)	
Mutual interference prevention	-	YES	YES	
Operation mode	Light ON mode - Dark ON mode selectable (Adjuster)			
Indicator	Operation indicator (yellow), stability indicator (green), power indicator (red) <sup>04)</sup>			
Approval	CE	CE	CE	

01) Reflector (MS-2S)

02) Non-glossy white paper 100 × 100 mm

03) Non-glossy white paper 300 × 300 mm

04) Only for the emitter

Unit weight (packaged)	Through-beam	Polarized retroreflective	Diffuse reflective
Cable type	≈ 95 g (≈ 145 g)	≈ 50 g (≈ 115 g)	≈ 50 g (≈ 100 g)
Cable connector type	≈ 55 g (≈ 105 g)	≈ 30 g (≈ 95 g)	≈ 30 g (≈ 80 g)
Power supply	10-30 VDC≡ ±10 % (ripple P-P: ≤ 10 %)		
Current consumption	It depends on the sensing type		
Through-beam	Emitter: ≤ 20 mA, receiver: ≤ 20 mA		
Reflective	≤ 30 mA		
Control output	NPN open collector output / PNP open collector output model		
Load voltage	≤ 30 VDC≡		
Load current	≤ 100 mA		
Residual voltage	NPN: ≤ 1 VDC≡, PNP: ≤ 2 VDC≡		
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit		
Insulation resistance	≥ 20 MΩ (500 VDC≡ megger)		
Noise immunity	±240 VDC≡ the square wave noise (pulse width: 1 μs) by the noise simulator		
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min		
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours		
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times		
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx		
Ambient temperature	-25 to 60 °C, storage: -40 to 70°C (no freezing or condensation)		
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)		
Protection rating	IP67 (IEC standard), IP67G (JEM standard)		
Connection	Cable type / Cable connector type model		
Cable spec.	Ø 4 mm, 3-wire (emitter: 2-wire), cable type: 2 m, cable connector type: 300 mm		
Wire spec.	AWG26 (0.52 mm, 20-core), insulator outer diameter: Ø 1 mm		
Connector	M12 4-pin plug type		
Material	Case: ABS, CAP: PA12, sensing part: PMMA		

# Oil-Proof Photoelectric Sensors

## BJR-F Series



### Features

- Long sensing distance with lens of high performance: Through-beam type 15 m, diffuse reflective type 1 m, polarized retroreflective type 3 m (MS-2S)
- M.S.R. (Mirror Surface Rejection) function (Polarized retroreflective type)
- Compact size : W 11 × H 32 × L 20 mm
- Adjuster for Light ON / Dark ON mode
- Sensitivity adjustment Adjuster
- Built-in reverse polarity protection circuit and output short overcurrent protection circuit
- Mutual interference prevention function (except through-beam type)
- Excellent noise immunity and minimal influence from ambient light
- Stronger in the environment with full of cutting fluid or lubricating oil (optimized for automobile and machine tool industry)
- IP67 protection rating (IEC standard), IP67F oil proof protection rating (JEM standard)

### Specifications

Model	BJR□-TDT-□-□-F	BJR3M-PDT-□-□-F	BJR□-DDT-□-□-F
Sensing type	Through-beam	Polarized retroreflective	Diffuse reflective
Sensing distance	10 m      15 m	3 m <sup>01)</sup>	100 mm <sup>02)</sup> 1 m <sup>03)</sup>
Sensing target	Opaque materials	Opaque materials	Opaque materials, translucent materials
Min. sensing target	≥ Ø 12 mm	≥ Ø 75 mm	-      -
Hysteresis	-	-	≤ 20 % of sensing distance
Response time	≤ 1 ms		
Light source	Infrared      Red	Red	Red      Infrared
Peak emission wavelength	850 nm      660 nm	660 nm	660 nm      850 nm
Sensitivity adjustment	YES (Adjuster)	YES (Adjuster)	YES (Adjuster)
Mutual interference prevention	-	YES	YES
Operation mode	Light ON mode - Dark ON mode selectable (Adjuster)		
Indicator	Operation indicator (yellow), stability indicator (green), power indicator (red) <sup>04)</sup>		
Approval	CE	CE	CE

01) Reflector (MS-2S)

02) Non-glossy white paper 100 × 100 mm

03) Non-glossy white paper 300 × 300 mm

04) Only for the emitter

Unit weight (packaged)	Through-beam	Polarized retroreflective	Diffuse reflective
Cable type	≈ 95 g (≈ 145 g)	≈ 50 g (≈ 115 g)	≈ 50 g (≈ 100 g)
Connector type	≈ 12 g (≈ 65 g)	≈ 6 g (≈ 75 g)	≈ 6 g (≈ 60 g)
Cable connector type	≈ 55 g (≈ 105 g)	≈ 30 g (≈ 95 g)	≈ 30 g (≈ 80 g)
Power supply	10-30 VDC≒ ±10 % (ripple P-P: ≤ 10 %)		
Current consumption	It depends on the sensing type		
Through-beam	Emitter: ≤ 20 mA, receiver: ≤ 20 mA		
Reflective	≤ 30 mA		
Control output	NPN open collector output / PNP open collector output Model		
Load voltage	≤ 30 VDC≒		
Load current	≤ 100 mA		
Residual voltage	NPN: ≤ 1 VDC≒, PNP: ≤ 2 VDC≒		
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit		
Insulation resistance	≥ 20 MΩ (500 VDC≒ megger)		
Noise immunity	±240 VDC≒ the square wave noise (pulse width: 1 μs) by the noise simulator		
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min		
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours		
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times		
Ambient illuminance (receiver)	Sunlight: ≤ 11,000 lx, incandescent lamp: ≤ 3,000 lx		
Ambient temperature	-25 to 60 °C, storage: -40 to 70°C (no freezing or condensation)		
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)		
Protection rating	IP67 (IEC standard), IP67F (JEM standard)		
Connection	Cable type / Connector type / Cable connector type model		
Cable spec.	Ø 4 mm, 3-wire (Emitter: 2-wire), cable type: 2 m, cable connector type: 300 mm		
Wire spec.	AWG26 (0.52 mm, 20-core), insulator outer diameter: Ø 1 mm		
Connector	Connector type: M8 4-pin plug type, cable connector type: M12 4-pin plug type		
Material	Case: ABS, CAP: PA12, sensing part: PMMA		



View product detail

# Color Mark

## Photoelectric

## Sensors

### BC Series



#### Features

- Outstanding color matching accuracy
  - R.G.B light emitting diodes and 12-bit resolution
  - 2 detection modes (color only / color + intensity)
  - 3-step sensitivity adjustment for each mode (fine, normal, rough)
- External light interference reduction minimizes errors and allows stable detection
- Check reference color with teaching indicator
- Operation indicator (red), stability indicator (green), timer indicator (orange)
- Configure operation functions with external input from wiring
- W 1.24 × L 6.7 mm spot size for detection of tiny targets and color marks
- IP67 protection rating (IEC standard)

#### Specifications

Model	BC15-LDT-C-□
Sensing type	Convergent reflective
Sensing distance	15 mm ± 2 mm
Sensing target	Opaque materials, translucent materials
Hysteresis	≤ 20 % of sensing distance (may vary by sensing mode or sensitivity)
Response time	≤ 500 μs
Light source	Full Color (Red, Green, Blue)
Min. spot size	W 1.24 × L 6.7 mm
Sensing mode	C mode (color only) - C+I mode (color + intensity) selectable (SET key or SET cable)
Sensitivity adjustment	YES (SET key or SET cable)
Operation mode	Color match (Normally Open) - Color mismatch (Normally Closed) mode selectable (Adjuster)
Teaching	YES
Timer	OFF-delay mode: 40 ms
Indicator	Operation indicator (red), stability indicator (green), teaching indicator (full color), timer indicator (orange)
Approval	CE ENEC
Unit weight (packaged)	≈ 14 g (≈ 80 g)
Power supply	12-24 VDC= ±10 % (ripple P-P: ≤ 10 %)
Current consumption	≤ 30 mA
Control output	NPN open collector output / PNP open collector output model
Load voltage	≤ 30 VDC=
Load current	≤ 100 mA
Residual voltage	NPN: ≤ 1 VDC=, PNP: ≤ 2.5 VDC=
Protection circuit	Reverse power protection circuit, output short overcurrent protection circuit
Insulation resistance	≥ 20 MΩ (500 VDC= megger)
Noise immunity	±240 VDC= the square wave noise (pulse width: 1 μs) by the noise simulator
Dielectric strength	1,000 VAC~ 50/60 Hz for 1 min
Vibration	1.5 mm double amplitude at frequency of 10 to 55 Hz (for 1 min) in each X, Y, Z direction for 2 hours
Shock	500 m/s <sup>2</sup> (≈ 50 G) in each X, Y, Z direction for 3 times
Ambient illuminance (receiver)	Incandescent lamp: ≤ 3,000 lx
Ambient temperature	-10 to 55 °C, storage: -25 to 75 °C (no freezing or condensation)
Ambient humidity	35 to 85 %RH, storage: 35 to 85 %RH (no freezing or condensation)
Protection rating	IP67 (IEC standard)
Connection	Connector type
Connector	M12 4-pin plug type
Material	Case: PC, sensing part: Acrylic, bracket: SUS304, bolt: Carbon Steel



View product detail